

120° Angle Bars with Exposed Flanges

Flat 2 Hole Exposed Flange

SPECIFICATION: (Stainless Steel)

120° Angle Bar 12" x 12" (305 x 305 mm) with Flat 2 hole exposed flanges. Manufactured by ELCOMA from 18 gauge, Type 304, satin finished, stainless steel tubing. Two, 12 gauge stainless steel mounting flanges shall be Heliarc welded to the tube to form a single structural unit. Angle Bar shall comply with all applicable federal, and local building and safety codes.

Flat 2 Hole "F"
Exposed Flange



1.25" (32 mm) bar dia.
1.50" (38 mm) bar dia.

Model # 12-221212SF
Model # 12-521212SF

(substitute S with K for Knurled grip,
P for Peened grip, or G for SHUR-GRIP)

SPECIFICATION: (Stainless Steel with center post)

120° Angle Bar with center post and Flat 2 hole exposed flanges. Manufactured by ELCOMA from 18 gauge, Type 304, satin finished, stainless steel tubing. Three, 12 gauge stainless steel mounting flanges shall be Heliarc welded to the tube to form a single structural unit. Angle Bar shall comply with all applicable federal, and local building and safety codes.

(* insert standard size 1616, 1818 or 2424)

1.25" (32 mm) bar dia.
1.50" (38 mm) bar dia.

Model # 13-22*SF
Model # 13-52*SF

(substitute S with K for Knurled grip,
P for Peened grip, or G for SHUR-GRIP)

SPECIFICATION: (Painted Stainless Steel)

120° Angle Bar 12" x 12" (305 mm x 305 mm) with Flat 2 hole exposed flanges. Manufactured by ELCOMA from 18 gauge, Type 304, stainless steel tubing. Two, 12 gauge stainless steel mounting flanges shall be Heliarc welded to the tube to form a single structural unit. Angle Bar shall have a painted finish. It shall comply with all applicable federal, and local building and safety codes.

1.25" (32 mm) bar dia. White	Model # 12-261212SF01	(substitute S with G for SHUR-GRIP)
1.25" (32 mm) bar dia. Almond	Model # 12-261212SF02	" "
1.50" (38 mm) bar dia. White	Model # 12-561212SF01	" "
1.50" (38 mm) bar dia. Almond	Model # 12-561212SF02	" "

SPECIFICATION: (Painted Stainless Steel with center post)

120° Angle Bar with center post and Flat 2 hole exposed flanges. Manufactured by ELCOMA from 18 gauge, Type 304, stainless steel tubing. Three, 12 gauge stainless steel mounting flanges shall be Heliarc welded to the tube to form a single structural unit. Angle Bar shall have a painted finish. It shall comply with all applicable federal, and local building and safety codes.

(* insert standard size 1616, 1818 or 2424)

1.25" (32 mm) bar dia. White	Model # 13-22*SF01	(substitute S with G for SHUR-GRIP)
1.25" (32 mm) bar dia. Almond	Model # 13-22*SF02	" "
1.50" (38 mm) bar dia. White	Model # 13-52*SF01	" "
1.50" (38 mm) bar dia. Almond	Model # 13-52*SF02	" "

